

HEM SAW

DC 2038 Series

Dual Column Band Saw Machines

www.metalsaw.com 713.697.1605



Optional Features:

Chip Conveyor System
Cut Watcher System
Hydraulic Computer Controlled Traverse (HCCT)
Laser Light System
Semi-Automatic Operation
Telescoping Roller Table – Input Side
Telescoping Roller Table – Output Side
Top Clamp (Available Input & Output Sides)

Features:

- 2° Permanent Arm Tilt
- Adjustable Clamping Force
- Adjustable Cutting Force
- Adjustable Feed Rate
- Blade Brush
- Broken Blade Indicator
- Carbide Blade Guides
- Flood Coolant System w/ Wash-Down Hose
- Height Adjusted from Console
- Lock Out – Tag Out System
- Pedestal Console w/ 30' Umbilical – Manual Control
- Powered Blade Tension
- Powered Guide Arm
- Powered Miter
- Push Button Blade Speed w/ LED Readout
- Rotary Table for Base to Pivot
- Safety Guards
- Vises on Both Sides of the Blade

SPECIFICATIONS

SPECIFICATIONS	
Cutting Capacity	38" W x 20" H
Motor	15 HP
Blade Size	24'6" x 2" x .063" www.metalsaw.com
Blade Speeds	Variable Speed

PROUDLY DISTRIBUTED BY:



Metal Sawing Technology®

713.697.1605